


LÚČOVÉ TRYSKY

PARAMETRE

- Nastaviteľná výseč 25° – 360°
- V ponuke 2 možnosti nastavenia dostreku
- Nižšia rýchlosť zavlažovania zabraňuje stekaniu
- Viac lúčov pre rovnomernejšie pokrytie

CHARAKTERISTIKA SPRAYOVÝCH TRYSKIEK S-8A

Výseč	Tlak		Dostrek m	Prietok		Zráž. v. mm/h	
	bar	kPa		m ³ /h	l/min	■	▲
90° 	1,0	100	2,1	0,05	0,9	52	60
	1,5	150	2,2	0,07	1,1	55	64
	2,0	200	2,4	0,08	1,4	57	66
	2,1	210	2,4	0,09	1,4	57	66
	2,5	250	2,6	0,10	1,6	58	67
180° 	1,0	100	2,1	0,12	1,9	55	63
	1,5	150	2,2	0,13	2,1	51	58
	2,0	200	2,4	0,14	2,3	47	54
	2,1	210	2,4	0,14	2,3	46	53
	2,5	250	2,6	0,15	2,4	44	50
360° 	1,0	100	2,1	0,24	4,0	56	65
	1,5	150	2,2	0,25	4,2	50	58
	2,0	200	2,4	0,26	4,4	45	52
	2,1	210	2,4	0,26	4,4	44	51
	2,5	250	2,6	0,27	4,6	41	47

Tučné písmo = Odporúčany tlak

CHARAKTERISTIKA SPRAYOVÝCH TRYSKIEK S-16A

Výseč	Tlak		Dostrek m	Prietok		Zráž. v. mm/h	
	bar	kPa		m ³ /h	l/min	■	▲
90° 	1,0	100	4,3	0,08	1,4	18	21
	1,5	150	4,6	0,10	1,6	18	21
	2,0	200	5,0	0,11	1,9	18	21
	2,1	210	5,0	0,11	1,9	18	21
	2,5	250	5,3	0,13	2,1	18	21
180° 	1,0	100	4,3	0,14	2,3	14	17
	1,5	150	4,6	0,17	2,8	15	18
	2,0	200	5,0	0,20	3,3	16	18
	2,1	210	5,0	0,20	3,4	16	19
	2,5	250	5,3	0,23	3,8	16	19
360° 	1,0	100	4,3	0,23	3,9	12	14
	1,5	150	4,6	0,30	5,0	14	16
	2,0	200	5,0	0,36	6,1	15	17
	2,1	210	5,0	0,38	6,3	15	17
	2,5	250	5,3	0,43	7,2	16	18

Tučné písmo = Odporúčany tlak

LÚČOVÉ TRYSKY



S-8A

Dostrek: 2,1 m až 2,6 m



S-16A

Dostrek: 4,3 m až 5,3 m

S-8A

